

Rubio WoodCream Industrial Diluent Concentrate

Rubio WoodCream Industrial Diluent Concentrate is a concentrate developed for finetuning Rubio WoodCream on industrial coating lines. Rubio WoodCream Industrial Diluent Concentrate should be diluted **with water** to a ratio of 1:9.

Available soon



ATTENTION

Rubio WoodCream Industrial Diluent Concentrate should be diluted with water.

PRODUCT INFORMATION

› Specific characteristics

- Reduces the viscosity
- Reduces the foam from overspray recuperation
- Prevents the drying of overspray recuperation
- Improves the flow for handheld spray guns
- Reduces the solid content

› Technical characteristics

- Physical state: liquid
- Color: light opaque – yellow
- pH: 7.5
- Density: 962.8 g/L

› Storage

The product can be stored up to 24 months. Store in dry conditions and in the original packaging. Do not allow to freeze.

› Packaging

- Jerrycan 1 L, 5 L

APPLICATION INFORMATION

› Instructions for use

Industrial application

Rubio WoodCream Industrial Diluent Concentrate can be used on the following industrial machines: vacuum coater and spray coating.

Vacuum coater

For operating the vacuum coater, follow the operational instructions of the manufacturer. Use Rubio WoodCream Industrial Diluent Concentrate to adjust the viscosity and fine-tune Rubio WoodCream when used on industrial coating lines. Rubio WoodCream Industrial Diluent Concentrate should be diluted **with water** to a ratio of 1:9.

Please consult the technical data sheet of Rubio WoodCream Industrial Application before use.

- Step 1.** Stir Rubio WoodCream Industrial Diluent Concentrate well.
- STEP 2.** Add the 1 part Rubio WoodCream Industrial Diluent Concentrate to 9 parts water and mix well.
- STEP 3.** Mix Rubio WoodCream well.
- STEP 4.** Add 1 part of the diluted material to 3 parts Rubio WoodCream.
- STEP 5.** Mix until becoming a homogenous product.

Spray coating

Rubio WoodCream is sprayable with an air mix spray gun. The spray gun or multiple guns can be installed in a narrow spray cabin (one plank at a time), or a wide belt (multiple planks at a time) spray cabin. The installation should be equipped with preferably nylon wiping brushes. Depending on the nozzle size of the airless pump, Rubio WoodCream should be diluted with Rubio WoodCream Industrial Diluent Concentrate between 10 and 50%.

Please consult the technical data sheet of Rubio WoodCream Industrial Application before use.

- Step 1.** Stir Rubio WoodCream Industrial Diluent Concentrate well.
- STEP 2.** Add the 1 part Rubio WoodCream Industrial Diluent Concentrate to 9 parts water and mix well.
- STEP 3.** Mix Rubio WoodCream well.
- STEP 4.** Add 1 part of the diluted material to 9 parts Rubio WoodCream (or a maximum of 1 part of the diluted material with 1 part Rubio WoodCream).
- STEP 5.** Mix until becoming a homogenous product.

› Related products



Check the packaging and the safety data sheet for more details.

For our complete assortment of products for the protection and coloring of interior and exterior wood, please visit www.rubimonocoatusa.com

YOUR DISTRIBUTOR:

LIABILITY: It is the user's responsibility to establish, through his own tests, whether the product is suitable for the chosen application. In no case can Muylle Facon BV be held liable for any consequential damage. The information above may be subject to changes, which will be published in the updated versions of the technical data sheet. We cannot be held liable for poor results due to causes that are not related to the quality of the product. This technical information has been drawn up based on the currently available information and knowledge. The most recent technical data sheets can be requested or are available on the website. **Date of TDS: 16/04/2021. Check the safety information before using the product.**



Rubio[®] MONOCOAT

MUYLLE  FACON

Muylle Facon BV
Ambachtenstraat 58
8870 Izegem (BELGIUM)

Phone +32 (0) 51 30 80 54
Fax +32 (0) 51 30 99 78
info@muyllefacon.be

www.rubimonocoat.com